

**MONGLA CEMENT FACTORY**  
**MONGLA, BAGERHAT**

(An Industrial Unit of Sena Kalyan Sangstha)  
Cell: 01769 056 316, PABX: 880-02-55058408  
E-mail: [dpd@senakalyan.com](mailto:dpd@senakalyan.com)

**RE- TENDER NOTICE**

Mongla Cement Factory (MCF) is interested to procure the following items for cement production:

- a) Limestone : **7,000 MT** (Supply by End of March 2026)
- b) Slag : **8,000 MT** (Supply by 15 March 2026).
- c) Rate/offer : To be quoted as “**CFR CTG / MONGLA**” per MT basis.
- d) **Insurance, Stevedoring, Customs Duty & River Dues** at Buyer’s A/c .
- e) **Performance Guarantee (PG)**: 2.5% of contract value to be submitted before LC opening.
- f) **LC Opening Bank**: The Trust Bank PLC, Sena Kalyan Bhaban Branch, Motijheel, Dhaka
- g) **Specification attached 2 separate sheet**

Detail tender schedule will be available in the Business Division-1, Sena Kalyan Sangstha, SKS TOWER (Level 5), 7 VIP Road, Mohakhali, DHAKA-1206, upon payment of **Tk 2,000/-** (Non-refundable) in cash for each item during office hours.

Offers are to be dropped in the tender box kept in the office of Business Division-1, at the above address before **10/03/2026 by 10:00 hours BST** and will be opened on the same day at **10:05 hour BST** in the presence of Bidders (if there are any). Sena Kalyan Sangstha reserves the right to accept or reject any or all tenders without assigning any reason whatsoever.

General Information : 01769 056 316

DATE: **02 March 2026**

**Director General**  
Business Division-1  
Sena Kalyan Sangstha

## SPECIFICATION OF GRANULATED BLAST FURNACE SLAG

Sl. No	Parameters/Composition	Percentage
01.	Moisture	10% Max
02.	Calcium Oxide (CaO)	30-45%
03.	Silicon di Oxide (SiO <sub>2</sub> )	30-35%
04.	Aluminum Oxide (Al <sub>2</sub> O <sub>3</sub> )	12- 20%
05.	Ferric Oxide (Fe <sub>2</sub> O <sub>3</sub> )	1% Max
06.	Magnesium Oxide (MgO)	5-9%
07.	Sulphuric Anhydride (SO <sub>3</sub> )	1% Max
08.	Insoluble Residue (IR)	0.50% Max
09.	Loss on Ignition	1% Max
10.	Glass Content	95% Min



*Rdmmmmmm*  
Md Rezaul Hossain  
Dy. Manager (BD-1)  
Business Division-1  
Sena Kalyan Sangstha

## SPECIFICATION OF LIMESTONE

Sl. No	Parameters/Composition	Percentage
01.	Moisture	2% Max
02.	Size	25 mm Max
03.	Calcium Oxide (CaO)	47.6% Min
04.	Silicon di Oxide (SiO <sub>2</sub> ) & Insoluble Residue (IR)	4% Max
05.	Purity of Limestone (CaCO <sub>3</sub> )	85% Min



*R. Hossain*  
Md Rezaul Hossain  
Dy. Manager (BD-1)  
Business Division-1  
Sena Kalyan Sangstha

Md Rezaul Hossain