



# Mongla Cement Factory

(A Project of Sena Kalyan Sangstha)

Cell: 01769 056 516, PABX: 880-02-55058408

(Sun-Thu, 9am-4pm)

## RE -TENDER NOTICE FOR SUPPLY OF RAW MATERIALS FOR CEMENT PRODUCTION

1. Mongla Cement Factory (MCF) is interested to procure/import the following item for production of Cement:

a) Descriptions :

Item	Qnt	ETA/ Supply Schedule	Tender Schedule BD T
Gypsum	5,000 MT	By 10 June 2026	2,000.00 (Non refundable)
Slag	10,000 MT	3rd Week of June 2026	
Limestone	10,000 MT	Last Week of June 2026	

b) Performance Guarantee (PG) : 2.5 % of Contract Value, submission before LC opening.

c) LC type: Sight LC (UPAS), LC payment will be released after testing of goods in Mongla Cement Factory Lab.

d) Bangladeshi agent has to submit the exporter's authorization letter with the offer.

2. Item wise offers are to be dropped in the tender box kept in the office of Sena Kalyan Sangstha, Business Division-1 , SKS Tower, Lift no 15 , Level 5 , Mohakahli, Dhaka by **18 May 2026** at 11.00 hr at the above address and will be opened on the same day 11.05 hour BST in the presence of Bidders (if there are any).

3. Sena Kalyan Sangstha reserves the right to accept or reject any or all tenders without assigning any reason whatsoever.

DATE: 10 May 2026

Director General  
Business Division -1  
Sena Kalyan Sangstha

## SPECIFICATION OF LIMESTONE

Sl. No	Parameters/Composition	Percentage
01.	Moisture	2% Max
02.	Size	25 mm Max
03.	Calcium Oxide (CaO)	47.6% Min
04.	Silicon di Oxide (SiO <sub>2</sub> ) & Insoluble Residue (IR)	4% Max
05.	Purity of Limestone (CaCO <sub>3</sub> )	85% Min



## SPECIFICATION OF NATURAL GYPSUM

Sl. No	Parameters/Composition	Percentage
01.	Moisture	2% Max
02.	Size	50 mm Max
03.	Silicon di Oxide (SiO <sub>2</sub> ) & insoluble matter	2% Max
04.	Sulphuric Anhydride (SO <sub>3</sub> )	42% Min
05.	Calcium Oxide (CaO)	30.6% Min
06.	Magnesium Oxide (MgO)	0.5% Max
07.	P <sub>2</sub> O <sub>5</sub>	0.5% Max
08.	Chloride	0.5% Max
09.	Purity of Gypsum (as CaSO <sub>4</sub> )	90% Min



## SPECIFICATION OF GRANULATED BLAST FURNACE SLAG

Sl. No	Parameters/Composition	Percentage
01.	Moisture	10% Max
02.	Calcium Oxide (CaO)	30-45%
03.	Silicon di Oxide (SiO <sub>2</sub> )	30-35%
04.	Aluminum Oxide (Al <sub>2</sub> O <sub>3</sub> )	12- 20%
05.	Ferric Oxide (Fe <sub>2</sub> O <sub>3</sub> )	1% Max
06.	Magnesium Oxide (MgO)	5-9%
07.	Sulphuric Anhydride (SO <sub>3</sub> )	1% Max
08.	Insoluble Residue (IR)	0.50% Max
09.	Loss on Ignition	1% Max
10.	Glass Content	95% Min

